



CALL TOLL FREE

877-763-1471

808

EXPOSED STRUCTURE CLEANING SOLUTION

HEAVY DUTY - OXYGEN ENHANCED

Our Exclusive Heavy Duty - Oxygen Enhanced Exposed Structure Cleaner is Non-Toxic, Biodegradable, Odorless and Phosphate-free. This Green Cleaning product releases Oxygen bubbles that devours organic stains and odors imbedded in all water safe surfaces.

Made especially for the most difficult to remove soils such as mold, mildew, food and body oils, nicotine and other stains and odors from all types of non-porous acoustical ceilings, walls, exposed structures and many other water safe surfaces.

Meets or exceeds GS-37 environmental standards
for industrial and institutional cleaners.



OXYGEN ENHANCED
GREEN CLEANING PRODUCT

EXPOSED STRUCTURE CLEANER

Makes
53
Gallons!

For Superior Results when cleaning non-porous acoustical ceiling and open structures. **Always test surface first before applying solution.** Use Professional Ceiling Sprayer and apply at 50-100 psi, using flat-fan spray tips. Remove Soot and heavy dust build-up before spraying. Cover all equipment and area other than ceiling or area to be sprayed prior to spraying. Evenly wet the surface. Do not over wet surface to a point where solution runs or drips off. Extremely stained or heavily soiled surfaces may require several applications. Always store in vented OSHA approved container.

Shipping Weight: 46 lbs. Shipping Size: 13" x 13" x 16.5"

FEATURES AND BENEFITS:

- Meets or Exceeds GS-37 Standards
- FD & C Dyes
- Low V.O.C's
- Phosphate Free
- Non Combustible
- No Glycol Ethers
- No Nonyl Phenols
- No Carcinogens
- Recyclable Packaging
- No Petroleum Distillates
- No Ozone Depleting Compounds
- Made from Renewable Resources (Vegetable Derived)
- Non Toxic: Non Sara 313 Chemicals
- Non Corrosive: pH not lower than 4, not higher than 10
- Aquatic Toxicity (LC50 < 100mg/L)
- Exceeds Current Regulatory Requirements

MIXING INSTRUCTIONS:

STEP 1

Shake or Mix 5 gallon pail of EXPOSED STRUCTURE CLEANER for several minutes.

STEP 2

Mixing ratio is 12-18 ounces per gallon of water. Use properly vented OSHA approved container.

STEP 3

Pour into an OSHA approved container the proper ratio of EXPOSED STRUCTURE CLEANER to Water and Mix well, before applying.

STEP 4

Pour mixed solution into your professional sprayer, container or spray bottle and apply.

Normal Cleaning: To clean Tile, Grout, Sinks, Urinals, Shower Stalls, Toilets, and Floors. Spray, wipe or mop on surfaces to be cleaned. Allow Cleaner to penetrate for a few minutes. Rinse off or wipe dry.

Heavy Duty Cleaning: For heavily encrusted soils and grease, agitate with a brush or mild scrubbing pad. Rinse, Wipe Dry, Mop up or Wet Vacuum.

OTHER RECOMMENDED USES:

- Toilets and Urinals
- Counter Tops
- Tile and Grout
- Non-Porous Ceiling Tiles
- Carpet Spots and Stains
- Concrete, Marble, and Stone
- Bathtubs
- Showers
- Floors
- Upholstery
- Glass

PRODUCT ID: PM-808
PRODUCT NUMBER: 808
PRODUCT NAME: Exposed Structure
Cleaning Solution

© COPYRIGHT 2013 All Rights Reserved.
CARUSO CARE - NCWLN